

Series: AXIAL-FAN Type A/AW

**FISCHBACH**

Luft- und Ventilatorentechnik GmbH

Type: **AW500/D500**

**ERP** KONFORM



**Forgalmazó:**  
Oxyma Systems Kft.  
3433 Nyékládháza, Ady Endre u. 49/A


phone: +36 (30) 665-5982  
internet: [www.fischbach-air.hu](http://www.fischbach-air.hu)  
email: [oxyma@oxyma.hu](mailto:oxyma@oxyma.hu)

available: - only aggregate  
- with square wall frame, with grids  
- with round wall frame, with grids  
- with double-flange pipe

### Technical Data

weight:	(kg)	20
material housing:		steel, galvanized
material impeller:		plastic
direction of rotation:		left
protection class:		IP 65
insulation class:		F
motor protection:		thermal contact

connection plan  
0.13-2 I.



the silent one



**Type: AW500/D500**

Erp 2013 2015 x 2018


**Performance data**

main voltage:	(V)	400 (3~)
frequency:	(Hz)	50
current max.:	(A)	1,6
power input max.:	(kW)	0,61
air flow volume max.:	(m³/h)	9577
statical pressure max.:	(Pa)	124
speed max.:	(rpm)	1309
supply air temperature:	(°C)	-25... +60
capacitor:	(µF)	-

\* aggregate/square-/round wall frame/double-flange pipe

**ErP-Data:**

total efficiency fan ( $\eta_e$ ):	(%)	33,7
installation category:		A
efficiency category:		static
efficiency grade: N	(%)	40
target efficiency ( $\eta_{target}$ ):	(%)	32,3
speed controller		no
year of manufacturing		since 2015
manufacturer:	Fischbach Luft- und Ventilatorentechnik GmbH D-57290 Neunkirchen / HRB 5804 Siegen	
order no. *	18030247/18030447/18030347/18030547	
power input:	(kW)	0,61
air flow volume:	(m³/h)	6374
statical pressure:	(Pa)	116
speed:	(rpm)	1294
specific ratio:		1
disassembling/recycling/disposal:	see page decommission	
installation/operation/maintenance:	see operating and mounting instructions	
measurement for determination of efficiency without additional items		



**Speed controller / accessories / sound data**, please see in the appropriate table

Technical documentation according to page: **General information**